



Product

Torque Machine

Stroking Unit

KEY FEATURES

- ✓ Increased stroke offering, Torque by rotating the head approx. 45 degrees (Additional 15 degrees over Std units)
- ✓ Top open Tailstock option allows safe, efficient loading & unloading of tubulars
- ✓ Low hydraulic working pressure
- ✓ Standalone hydraulic power pack that can be situated up to 10 metres away from the Torque machine
- ✓ Electronic control desk
- ✓ Standard Torque ratings up to 200,000 ft lbs
- ✓ Fully programmable support jacks to ensure pipe alignment
- ✓ Torque v Time real time graph recording
- ✓ Capable of clamping 2.3/8" diameter upwards
- ✓ Automatic Torque control

EnerQuip's range of High Torque Stroking Machines (SM) are designed for fast and accurate, horizontal make-up and break-out of threaded connections.

The EnerQuip SM machine has been designed with the ever changing industry requirements for more accurate data, cost and time saving

- ✓ Low torque ability as standard circa. 100 ft lb
- ✓ Automated self-leveling tool support jacks
- ✓ Multiple graph overlay and make-up trend instantly highlights any anomalies in make-up



AUTOMATIC TORQUE CONTROL

The advanced control system behind our SM machine allows the operator to make up a connection in automatic.

In automatic mode the machine will clamp – rotate – unclamp – re-stroke the torque rams – and repeat until the connection is made up to the optimum torque. This feature has been proven to increase productivity through the machine.



SUPPORT 24/7 365 DAYS A YEAR

We offer remote or local support whenever and wherever required – for your breakdown, service, calibration and repair requirements.

24/7 SUPPORT 24/7/365



E-Mail:

Sales@EQtorque.com



Call UK:

+44 (0)1224 608 628



Call USA:

+1 (713) 936 9393



Visit:

www.EQtorque.com